

**I CLAIM:**

1. A boat misting system comprising:
  - a screened water inlet for covering an opening in the  
5 side of a boat;  
said screened water inlet positionable within a water  
source;  
a filter connectable to said water inlet and  
concealable below a deck of the boat;  
10 supply piping connectable to the inlet and the filter  
and concealable below the deck of the boat;  
a water pump, connectable to said filter with said  
supply piping, for drawing water through said water  
inlet and said filter;  
15 said water pump concealable below the deck of the  
boat;  
said water pump connectable to a control panel;  
a supply outlet manifold concealable below the deck  
and extendable from said water pump to a portion of  
20 the boat;

a plurality of supply lines connectable to said supply  
outlet manifold; and

a plurality of independently adjustable pressure and  
adjustable tilt angle spray nozzles installable

5 at intervals along said supply lines.

2. The boat misting system of claim 1, wherein each  
said spray nozzle has a swivel joint and a mist control  
tip.

3. The boat misting system of claim 1, wherein the  
10 control panel has a timer for cycling the pump.

4. The boat misting system of claim 1, wherein said  
supply lines are concealable within a hull of the boat.

5. The boat misting system of claim 1 further  
comprising a plurality of reducers for connecting said  
15 supply outlet manifold to said supply lines.

6. The boat misting system of claim 1 further  
comprising quick disconnects for attaching a length of  
extension tubing with a plurality of said spray nozzles for  
the purpose of extending a portion of said misting system  
20 to a canopy frame.

7. A boat misting system comprising:

a screened water inlet for covering an opening in the side of a boat;

said screened water inlet positionable within a water source;

5 a filter connectable to said water inlet and concealable below a deck of the boat;

supply piping connectable to the inlet and the filter and concealable below the deck of the boat;

a water pump, connectable to said filter with said  
10 supply piping, for drawing water through said water inlet and said filter;

said water pump concealable below the deck of the boat;

said water pump connectable to a control panel;

15 a supply outlet manifold concealable below the deck and extendable from said water pump to a portion of the boat;

a plurality of supply lines concealable in a boat hull and connectable to said supply outlet manifold; and

a plurality of independently adjustable pressure and adjustable tilt angle spray nozzles protruding from the boat hull at intervals along said supply lines.

8. The boat misting system of claim 7, wherein each  
5 said spray nozzle has a swivel joint and a mist control tip.

9. The boat misting system of claim 7, wherein the control panel has a timer for cycling the pump.

10. The boat misting system of claim 7 further  
10 comprising quick disconnect means for attaching a length of extension tubing with a plurality of said spray nozzles for the purpose of extending a portion of said misting system to a canopy frame.

11. A boat misting system comprising:  
15 a screened water inlet;  
a filter concealed under a deck of a boat;  
said filter connected to said water inlet;  
supply piping connected to said filter and concealed  
under the deck of the boat;  
20 a water pump concealed under the deck of the boat;

said water pump connected to said filter and in  
electronic communication with a control panel;  
a supply outlet manifold extended from said water pump  
and concealed under the deck or within a hull of the  
5 boat;  
a plurality of supply lines connected to said supply  
outlet manifold and concealed within the hull of the  
boat; and  
a plurality of independently adjustable pressure and  
10 adjustable tilt angle spray nozzles protruding from  
the boat hull at intervals along said supply lines.

12. Boat misting system of claim 11, wherein each  
said spray nozzle has a swivel joint and a mist control  
tip.

15 13. The boat misting system of claim 11, wherein the  
control panel has a timer for cycling the water pump.

14. The boat misting system of claim 11 further  
comprising quick disconnect means for attaching a length of  
extension tubing with a plurality of said spray nozzles for  
20 the purpose of extending a portion of said misting system  
to a canopy frame.

15. A method of cooling the atmosphere of a boat deck comprising:

activating a water pump via a control panel;

pumping water from a water source into a plurality of

5 supply lines which are concealed below a deck and

within a hull of a boat; and

expelling said water from said supply lines through a plurality of independently adjustable pressure and adjustable tilt angle spray nozzles.

10 16. A boat misting system comprising:

a screened water inlet for covering an opening in the side of a boat;

said screened water inlet positionable within a water source;

15 a filter connectable to said water inlet and

concealable within a wall of the boat;

supply piping connectable to the inlet and the filter and concealable below a deck and within the wall of the boat;

a water pump, connectable to said filter with said  
supply piping, for drawing water through said water  
inlet and said filter;  
said water pump concealable within the wall of the  
5 boat;  
said water pump connectable to a control panel;  
a supply outlet manifold concealable within the wall  
and extendable from said water pump to a portion of  
the boat;  
10 a plurality of supply lines concealable in a roof of  
the boat and connectable to said supply outlet  
manifold; and  
a plurality of independently adjustable pressure and  
adjustable tilt angle spray nozzles protruding from  
15 the boat roof at intervals along said supply lines.

17. The boat misting system of claim 16, wherein each  
said spray nozzle has a swivel joint and a mist control  
tip.

18. The boat misting system of claim 16, wherein the  
20 control panel has a timer for cycling the pump.